


Nuts For Shafts And Withdraw Sleeves (Series KM)

DIN 981 - ISO 2982



Type	Weight kg	Thread	d	D ¹	D ²	t	i	h	For Washer
KM 0	0.005	M10x0.75	10	18	13.5	4	3	2	MB 0
KM 1	0.007	M12x1	12	22	17	4	3	2	MB 1
KM 2	0.010	M15x1	15	25	21	5	4	2	MB 2
KM 3	0.013	M17x1	17	28	24	5	4	2	MB 3
KM 4	0.019	M20x1	20	32	26	6	4	2	MB 4
KM 5	0.025	M25x1.5	25	38	32	7	5	2	MB 5
KM 6	0.043	M30x1.5	30	45	38	7	5	2	MB 6
KM 7	0.053	M35x1.5	35	52	44	8	5	2	MB 7
KM 8	0.085	M40x1.5	40	58	50	9	6	2.5	MB 8
KM 9	0.120	M45x1.5	45	65	56	10	6	2.5	MB 9
KM 10	0.150	M50x1.5	50	70	61	11	6	2.5	MB 10
KM 11	0.160	M55x2	55	75	67	11	7	3	MB 11
KM 12	0.170	M60x2	60	80	73	11	7	3	MB 12
KM 13	0.200	M65x2	65	85	79	12	7	3	MB 13
KM 14	0.240	M70x2	70	92	85	12	8	3.5	MB 14
KM 15	0.290	M75x2	75	98	90	13	8	3.5	MB 15
KM 16	0.400	M80x2	80	105	95	15	8	3.5	MB 16
KM 17	0.450	M85x2	85	110	102	16	8	3.5	MB 17
KM 18	0.560	M90x2	90	120	108	16	10	4	MB 18
KM 19	0.660	M95x2	95	125	113	17	10	4	MB 19
KM 20	0.700	M100x2	100	130	120	18	10	4	MB 20
KM 21	0.850	M105x2	105	140	126	18	12	5	MB 21
KM 22	0.970	M110x2	110	145	133	19	12	5	MB 22
KM 23	1.010	M115x2	115	150	137	19	12	5	MB 23
KM 24	1.080	M120x2	120	155	138	20	12	5	MB 24
KM 25	1.190	M125x2	125	160	148	21	12	5	MB 25
KM 26	1.250	M130x2	130	165	149	21	12	5	MB 26
KM 27	1.550	M135x2	135	175	160	22	14	6	MB 27
KM 28	1.560	M140x2	140	180	160	22	14	6	MB 28
KM 29	2.000	M145x2	145	190	172	24	14	6	MB 29
KM 30	2.030	M150x2	150	195	171	24	14	6	MB 30
KM 31	2.210	M155x3	155	200	182	25	16	7	MB 31
KM 32	2.590	M160x3	160	210	182	25	16	7	MB 32
KM 33	2.430	M165x3	165	210	193	26	16	7	MB 33
KM 34	2.800	M170x3	170	220	193	26	16	7	MB 34
KM 36	3.070	M180x3	180	230	203	27	18	8	MB 36
KM 38	3.390	M190x3	190	240	214	28	18	8	MB 38
KM 40	3.690	M200x3	200	250	226	29	18	8	MB 40

Also available in stainless steel.