

Timing Belts Rubber T2.5,T5,T10,T20, AT5, AT10 & D



The T Type tooth profile makes this belt well suited for use in positioning applications.

Markets/Applications

Suitable for office machines, machine tools, postage equipment, sewing machines, vending machines, agriculture, outdoor power equipment, food processing, HVAC, oil fields, wood, paper, sand and gravel applications.

Features/Advantages

- Fiberglass tensile cord provides high strength, excellent flex life, and high resistance to elongation.
- Neoprene body provides protection against grime, grease, oil and moisture.
- Nylon tooth facing provides a durable wear surface for long service life.
- Eliminates lubrication and re-tensioning to reduce maintenance and labor required on drives.
- Clean, quiet and smooth running operation.
- No lubrication required.

► Our available sizes including

Type	Pitch Pb(mm)	Tooth height ht(mm)	Belt thickness hs(mm)	Angle β°	Allowable min. Pulley Teeth Number Small Pulley Rotating Speed (r/Min)				
					<900	900~1200	1200~1800	1800~3600	3600~4800
T2.5 >>	2.5	0.7	1.3	40	10	12	14	16	18
T5 >>	5	1.2	2.2	40	10	10	12	12	15
T10 >>	10	2.5	4.5	40	12	12	14	16	18
T20 >>	20	5	8	40	22	24	26	30	-

The Min. Crimp Diameter Allowed

Type	T2.5	T5	T10	T20	AT5	AT10	AT20
Min. Crimp Diameter (mm)	15	15	20	40	15	20	40

Example of Mark

