

Dry V-belts With Aramid Cords



To meet with international environment-protection requirements, Ametric® aramid corded V belts with dry wrapping surface is featured with:

Aramid cord impregnated with special compound eliminates the need for re-tensioning while offering:

- High Tensile Strength
- Non-extensibility
- High Resistance to shock loads

Dry wrapping of special fabric ensures:

- High resistance to wear and tear and reduced slippage while clutching

Belt Characteristics ensure:

- High resistance to repeated reverse flexing
- High resistance to oil, heat and cracking

Extensive range tested and approved by many OEM's.

Available in **Blue**, **Brown**, **White**, **Grey**, and **Black** fabric.

Available in all standard sections.

As the name suggests, the applications using these belts are very specific.

Ametric® aramid corded V belts are also suitable for industrial applications where shock loading or zero elongation are critical factors. Typical applications include the lawn and garden Machinery where the clutching requirement is very high.

American Metric® Corporation
52 Metric Road * Laurens, S.C. 29360 USA * Tel No. (864)876-2011 * www.Ametric.com
engineering@ametric.com



▶ **Popular Brand Size/Product Number Comparison**

Ametric®	Jason	Carlisle PT	Gates	Goodyear	Dayco	Thermoid
ANSI	MXV	X-D-V	Powered	Insta-Power	GPL	Power Plus
3L-360	MXV3-360	38X360	6736	83360	L336	3H360
4L-380	MXV4-380	48X380	6838	84380	L438	4H380
5L-420	MXV5-420	58X420	6942	85420	L542	5H420

▶ **For Lawn and Garden Replacement Belts**