

# Heavy-Duty Raw Edge Cogged Metric V-Belts

| PROFILE X8 |        |        |        |        |        |        |
|------------|--------|--------|--------|--------|--------|--------|
| X8 160     | X8 335 | X8 400 | X8 490 | X8 575 | X8 670 | X8 750 |
| X8 280     | X8 340 | X8 425 | X8 495 | X8 580 | X8 680 | X8 775 |
| X8 300     | X8 350 | X8 430 | X8 530 | X8 600 | X8 700 | X8 800 |
| X8 315     | X8 355 | X8 450 | X8 550 | X8 630 | X8 710 |        |
| X8 322     | X8 375 | X8 475 | X8 560 | X8 655 | X8 717 |        |

| PROFILE X10 |         |         |         |         |          |          |          |
|-------------|---------|---------|---------|---------|----------|----------|----------|
| X10 290     | X10 460 | X10 540 | X10 660 | X10 790 | X10 900  | X10 1050 | X10 1250 |
| X10 315     | X10 475 | X10 560 | X10 670 | X10 800 | X10 925  | X10 1060 | X10 1295 |
| X10 375     | X10 480 | X10 575 | X10 680 | X10 820 | X10 940  | X10 1080 | X10 1300 |
| X10 380     | X10 500 | X10 590 | X10 710 | X10 825 | X10 950  | X10 1105 |          |
| X10 400     | X10 515 | X10 600 | X10 725 | X10 840 | X10 980  | X10 1150 |          |
| X10 425     | X10 520 | X10 615 | X10 750 | X10 850 | X10 1000 | X10 1200 |          |
| X10 440     | X10 525 | X10 630 | X10 765 | X10 865 | X10 1025 | X10 1215 |          |
| X10 450     | X10 530 | X10 650 | X10 772 | X10 875 | X10 1030 | X10 1225 |          |

| PROFILE X13 |         |         |         |          |          |          |          |
|-------------|---------|---------|---------|----------|----------|----------|----------|
| X13 400     | X13 535 | X13 690 | X13 780 | X13 900  | X13 1060 | X13 1220 | X13 1500 |
| X13 407     | X13 560 | X13 700 | X13 787 | X13 925  | X13 1075 | X13 1225 | X13 1525 |
| X13 457     | X13 580 | X13 710 | X13 800 | X13 950  | X13 1090 | X13 1350 | X13 1550 |
| X13 460     | X13 600 | X13 725 | X13 813 | X13 975  | X13 1100 | X13 1375 |          |
| X13 480     | X13 630 | X13 730 | X13 825 | X13 1000 | X13 1120 | X13 1400 |          |
| X13 483     | X13 650 | X13 750 | X13 850 | X13 1016 | X13 1150 | X13 1425 |          |
| X13 508     | X13 655 | X13 767 | X13 875 | X13 1030 | X13 1180 | X13 1450 |          |
| X13 530     | X13 670 | X13 775 | X13 889 | X13 1050 | X13 1200 | X13 1475 |          |

| PROFILE X17 |         |         |          |          |          |          |
|-------------|---------|---------|----------|----------|----------|----------|
| X17 630     | X17 762 | X17 850 | X17 965  | X17 1040 | X17 1215 | X17 1450 |
| X17 670     | X17 775 | X17 875 | X17 975  | X17 1060 | X17 1300 | X17 1475 |
| X17 710     | X17 800 | X17 900 | X17 1000 | X17 1075 | X17 1350 | X17 1500 |
| X17 725     | X17 825 | X17 925 | X17 1016 | X17 1163 | X17 1400 | X17 1525 |
| X17 750     | X17 840 | X17 950 | X17 1030 | X17 1180 | X17 1425 |          |

Ordering Example: X8 160      X8 ..... Profile      160..... Inside Length (mm)

Some sizes are available in heavy-duty raw edge cogged construction. Some available in heavy-duty raw edge only.

## High Temperature "HR" Belts

HR High Temperature Belts, that can stand up to 90 deg C / 194 deg F, can be special ordered in most profiles.

## Fire Resistant Anti-Static "FRAS" Belts

FRAS Fire Resistant Anti-static belts, can be special ordered.

## American Petroleum Institute Certified "API" Belts

API American Petroleum Institute Certified "API" Belts, can be special ordered.